







PROPOSAL



GOLD FLASH AREA (1u"max)



LED SCHEMATIC:

LEFT LED1:
LEFT LED2: GREEN
L4 + —> — L3

RIGHT LED1:
RIGHT LED2: GREEN
L2 + —> — L1

NOTES:

- MATERIAL:
HOUSING:HIGH TEMP.THERMOPLASTIC,BLACK,UL 94V-0
CONTACT:PHOSPHOR BORNEZE,T=0.35mm.
SHELL:SUS304 1/2H T=0.20mm
- FINISH:
CONTACT:50u"MIN. NICKEL UNDERPLATING ALL AREA,
100u"MIN. MATTE-TIN ON SOLDERTAILS,
GOLD PLATING ON CONTACT 6u".
- OPERATING TEMPERATURE:-40°C~+85°C.
- JACK CAVITY CONFORMS TO FCC RULES AND
REGULATIONS PART 68, SUBPART F

REV.	ECN. NO.	DRAWN	DATE	EC.content
A.0	NEW	Victor	12/16/2025	

ECONN
Technology
ECONN corporation

HSE
Compliant

⊗:QUALITY CONTROL ITEM		GENERAL TOLERANCE		PART NO.: JM8A-CH15-DA0Y		
APPROVED		.X±0.38	X'±2'	TITLE:RJ45 CONNECTOR 2*8 PORT W/LED, 8P8C, Shielded		
CHECKED		.XX±0.25	.X'±1'			
DRAWN		.XXX±0.13				
UNIT: mm		SCALE: 1:1		SHEET: 1/2	REV.: A.0	

説明: △: 備註 ◇: 版本變更 ⑨: 尺寸序號 ■: 重點尺寸 ▼: CPK 尺寸

DOCUMENT NO. : ZER0013/A.3

SIZE: A4

1 2 3 4 5 6 7 8

F

E

D

C

B

A

F

E


D

C


B

A


SIZE: A4



BACK VIEW



PCB LAYOUT TOLERANCE:±0.05



RECOMMENDED OPENING SIZE

P/N RULE:

JM8A-C H 1 5-D A 0 Y
SHELL CODE
H:W/ ALL SPRING
W/O LOGO
W/O BACK LEG
1:HSG PBT
LED CODE
LEFT LED1: GREEN
LEFT LED2: GREEN
RIGHT LED1: GREEN
RIGHT LED2: GREEN
Y: 一體式外殼
0 : SUS304 1/2H
DIM CODE
Contact PIN DIM A :3.30
LED PIN DIM B :3.30
PLATING CODE
D-GOLD PLATED 6u" MATTE-TIN

REV.	ECN. NO.	DRAWN	DATE	EC.content
A.0	NEW	Victor	12/16/2025	

ECONN
Technology
ECONN corporation

HSE
Compliant

◎:QUALITY CONTROL ITEM		GENERAL TOLERANCE		PART NO.: JM8A-CH15-DA0Y		
APPROVED		.X±0.38	X.'±2"	TITLE:RJ45 CONNECTOR 2*8 PORT W/LED, 8P8C, Shielded		
CHECKED		.XX±0.25	.X'±1"			
DRAWN		.XXX±0.13		UNIT: mm	SCALE: 1:1	SHEET: 2/2
				REV.: A.0		

1 2 3

說明: △: 備註 ◇: 版本變更 ⑨: 尺寸序號 ■: 重點尺寸 ▼: CPK 尺寸

DOCUMENT NO. : ZER0013/A.3